

Roalux Exterior Wall Primer

Product Description

Roalux Exterior Wall Primer is specially made for exterior surface with high coverage, brightness alkall resistance, atmosphere protection Anti-fungal. This will increase the durability of the exterior paint over on it. Does not require any water curing.

Features & Benefits

- Excellent Opacity
- Finish : MATT
- Washability : MEDIUM

Colors

Milky White

Packing

 1Lt
  4Lt
  10Lt
  20Lt
 Plastic Pails

Recommended Uses

AREA

Interior Exterior

SURFACES

- Exterior - Cement Plasters & Ceilings
- Asbestos Sheets Surfaces as an undercoat



Application Details & Surface Preparation

Tools	Mixing	Thinning	Thinning Ratio	Dry Timing
			85-90% 85-95% Volume	
Brush	Shake well before use	Water		Surface dry in 30 min
Cleaning	Environment	Surface	Application	Safety
				
Clean surface loose paint, dust with emery Paper Wipe clean soft cloth	Temp : 5-40 Dgr. Humi : Below 80%	Standard surface preparation required	Cleaning with water. Let it dry completely and apply a coat of REW min 5-6 hrs.	Non- flammable No added Lead Mercury / Chromium

www.roaluxpaints.com

91500 06666