

Acrylic Wall Putty

Interior Exterior **RAP**

Product Description

Roalux Acrylic Wall Putty is a water thinnable acrylic putty. It covers dent un even surface cracks and gives the uniform performance to the finished paint. Roalux Acrylic wall putty have excellent technologie modifier to give the easy workability.

Features & Benefits

- Smooth Finish
- Quick drying
- Finish : MATT
- Washability : NO

Colors

Super White



Packing



Plastic Pucket

Recommended Uses

AREA	SURFACES	1st COAT	2nd COAT
<input checked="" type="checkbox"/> Interior <input type="checkbox"/> Exterior	<ul style="list-style-type: none"> ■ Cement Plasters ■ Asbestos Sheets ■ Concrete etc., 	30 - 40 SQFT/KG	20 - 30 SQFT/KG

Application Details & Surface Preparation

Tools Putty Blade	Mixing Shake well before use	Coverage 30 - 40 sqft*	Thinning & Ratio Water Not Applicable	Dry Timing Surface Dry 30 Min
Cleaning Clean surface loose paint, dust with emery Paper Wipe clean soft cloth	Environment Temp : 10-40 Dgr. Humi : Below 80%	Surface Allow 3 months curing prior to painting for newly plasted surfaces. Allow to dry	Application Repeat sanding with abrasive paper. More coats if more smoother Surface. Give dry time.	Safety Non- flammable No added Lead Mercury / Chromium

* Practical spreading rate will vary from the quoted Theoretical spreading rate due to factors such as method and condition of application as well as surface roughness.