

Roalux Ceiling Emulsion

Interior Exterior **RCW**

Product Description

Roalux Ceiling Emulsion paint is specially formulated to provide minimal spatter and excellent coverage with High Brightness. It hides minor surface imperfection and dries quickly to give a smooth even finish.



Features & Benefits

- Uniform Finish
- High Brightness
- No Odour
- Finish : MATT
- Washability : LOW

Colors

White

Packing



Plastic Pails

Recommended Uses

AREA	SURFACES	1st COAT	2nd COAT
<input checked="" type="checkbox"/> Interior <input type="checkbox"/> Exterior	<ul style="list-style-type: none"> ■ Concrete ■ Plastered Wall ■ Interior, Etc., 	100 - 110 SQFT/LT	65 - 75 SQFT/LT

Application Details & Surface Preparation

Tools Brush, Spray & Roller	Mixing Mix well before use	Coverage 110 to 120 sqft*/single coat	Thining & Ratio 50-60% by Volume	Dry Timing Surface Dry 30 Min
Cleaning Clean surface loose paint, dust with emery Paper Wipe clean soft cloth	Environment Temp : 10-40 Dgr. Humi : Below 70%	Surface Sprinkle the surface with water	Application Apply 2-3 Coat 1 Lr of Emulsion 350-450 ml of Water	Safety Non- flammable No added Lead Mercury / Chromium

* Practical spreading rate will vary from the quoted Theoretical spreading rate due to factors such as method and condition of application as well as surface roughness.