

Roalux Exterior Wall Primer

☐ Interior ☒ Exterior **REW**

Product Description

Roalux Exterior Wall Primer is specially made for exterior surface with high coverage, brightness alkali resistance, atmosphere protection Anti-fungal. This will increase the durability of the exterior paint over on it. Does not require any water curing.

Features & Benefits

- Excellent Opacity
- Finish : MATT
- Washability : MEDIUM

Colors

☐ Milky White

Packing





 Plastic Pails



Recommended Uses

AREA

☐ Interior ☒ Exterior











SURFACES

- Exterior - Cement Plasters & Ceilings
- Asbestos Sheets Surfaces as an undercoat

 1 COAT

120 - 130
SQFT/LT

Application Details & Surface Preparation

Tools  Brush	Mixing  Shake well before use	Coverage  120 - 130 sqft*	Thining & Ratio  Water 85-90% 85-95% Volume	Dry Timing  Surface dry in 30 min
Cleaning  Clean surface loose paint, dust with emery Paper Wipe clean soft cloth	Environment  Temp : 5-40 Dgr. Humi : Below 80%	Surface  Standard surface preparation required	Application  Cleaning with water. Let it dry completely and apply a coat of REW min 5-6 hrs.	Safety  Non- flammable No added Lead Mercury / Chromium

* Practical spreading rate will vary from the quoted Theoretical spreading rate due to factors such as method and condition of application as well as surface roughness.