

# Superstar Acrylic Distemper

Interior  Exterior **STD**

## Product Description

Superstar Acrylic Distemper is specially made for interior surface with high coverage, brightness alkali resistance, atmosphere protection Anti-fungal. And available in pouch is an entry level distemper available in bright colors.

## Features & Benefits

- Excellent Opacity    ■ Economical
- Finish : MATT        ■ Washability : No

## Colors

As per shade card

## Packing



Plastic Pails  
Plastic Pouch



## Recommended Uses

<p><b>AREA</b></p> <p><input checked="" type="checkbox"/> Interior    <input type="checkbox"/> Exterior</p>	<p><b>SURFACES</b></p> <p>■ Plastered Walls</p>	<p> 1st COAT     2nd COAT</p> <p><b>110 - 120</b>    <b>65 - 75</b> SQFT/KG        SQFT/KG</p>
---	---	--

## Application Details & Surface Preparation

<p><b>Tools</b></p> <p>Brush &amp; Roller</p>	<p><b>Mixing</b></p> <p>Shake well before use</p>	<p><b>Coverage</b></p> <p>120 - 130 sqft*</p>	<p><b>Thining &amp; Ratio</b></p> <p>Water <span style="border: 1px solid red; border-radius: 50%; padding: 2px;">70%</span></p> <p>70% Volume</p>	<p><b>Dry Timing</b></p> <p>Surface dry in 20 min</p>
<p><b>Filling</b></p> <p>Roalux Putty</p>	<p><b>Environment</b></p> <p>Temp : 10-40 Dgr. Humi : Below 70%</p>	<p><b>Surface</b></p> <p>NA</p>	<p><b>Application</b></p> <p>Cleaning with water. Let it dry completely and apply a coat of REW min 5-6 hrs.</p>	<p><b>Safety</b></p> <p>Non- flammable No added Lead Mercury / Chromium</p>

\* Practical spreading rate will vary from the quoted Theoretical spreading rate due to factors such as method and condition of application as well as surface roughness.